

CP-AOCH/XL

Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated

| HDMI | 4K/60 UHD (4:2:0)



Kramer's CP-AOCH/XL is an Active Optical HDMI Cable for running 4K@60Hz (4:2:0), 4K@30Hz (4:4:4), over longer distances up to 100m (328ft) in a simple and practical way. The HDMI ends of this hybrid-fiber cable quickly detach leaving a much smaller head that can be run through conduit or other tight spaces with the included pulling capsule. DVI ends can be purchased separately. The AOCH cables are thinner, lighter and more flexible than copper or even standard optical cables. They provide transparent EDID and HDCP support without signal attenuation. They also provide reduced risk of EMI and RFI interference to provide a perfect solution for critical AV installations that demand the highest signal integrity

FEATURES

High Data Transfer Rate - Up to 10.2Gbps

Embedded Audio - PCM 8-channel, Dolby Digital True HD, DTS-HD Master Audio

High-Quality Connectors - 24K gold-plated, corrosion-resistant and best possible connectivity EMI & RFI Immunity

No External Power - Powers the active units via the HDMI connector, consumes only 0.25W (50mA @5V)

Thin Construction - 3.4mm (0.13") diameter

Small Bending Ratio - Only 6mm (0.24")

Jacket Construction - Low smoke & halogen free or UL CMP-OF (Plenum)

RoHS 2011/65/EU Compliant

Varied Selection of Lengths - Available in versions from 10 to 100m (32.8 to 328ft)



TECHNICAL SPECIFICATIONS

OVERALL VIDEO RESOLUTION: 4K @60Hz 4:2:0, 4K@30Hz 4:4:4, 8Bit, full HD, 3D Deep

Color

MAX. DATA RATE: Up to 10.2Gbps

SUPPORTED COLOR SPACES: RGB, YCbCr, xvYCC, Adobe sRGB, sYCC601

EMBEDDED AUDIO: Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio™,

DVD Audio, SA-CD

HDMI COMPLIANCE: HDCP 2.2, EDID, CEC

PHYSICAL CONNECTORS: Male HDMI Type D, 24K gold-plated

CABLE STRUCTURE: Hybrid optical fiber cable

FIBER OPTIC: Multi-mode fiber

CONDUCTORS: 6x28AWG (7/0.127mm)

OUTER SHEATH MATERIAL: LSHF or plenum

OUTER SHEATH COLOR: Blue

OUTER SHEATH DIAMETER: 3.4mm

CABLE BENDING RADIUS: 6mm

CONNECTOR MAX. PULLING STRENGTH: 22lbs (10kg)

MAX. COMPRESSION LOAD RESISTANCE: 500N (50kg, 110lbs)

ELECTRICAL POWER SUPPLY: No external power supply needed (draws current from the

source). If source power is not sufficient, connect the AD-HM/HF/UAM - USB to

HDMI power injector to an external power

POWER CONSUMPTION: 0.25W max

USAGE AND ENVIRONMENTAL

OPERATING TEMPERATURE: +32~+122°F (0~+50°C)

STORAGE TEMPERATURE: -22~+122°F (0~+50°C)

OPERATING HUMIDITY: 5 ~ 85%

REGULATORY LSHF (COMPLIANCE): IEC 60332-1, IEC 60754-1, IEC 61034-2

PLENUM (COMPLIANCE): CMP-OF

RoHS: 2011/65/ EU





CONFIGURATIONS

CP-AOCH/XL-33	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-50	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-66	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-98	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-131	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-164	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-197	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-230	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-262	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-295	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated
CP-AOCH/XL-328	Active Optical High-Speed Pluggable HDMI Cable - Plenum Rated