

EVA-44S-P

AC Charging Station (three phase)



LEADING - EDGE TECHNOLOGY

Three phase superfast AC charger for workplace or commercial use, single plug output

Features

 Programmable charging mode

 Compact and exquisite

 Comprehensive protection

 European Standard

 Multiple communication modes

 Flexible installation

Shenzhen Ateess Power Technology Co.,Ltd

1st Floor of Building 3 at Sector B and 3rd Floor of Building 9,Henglong Industrial Park, No.4 Industrial Zone, Shuitian Community, Shiyan Street, Baoan District, Shenzhen

Datasheet

EVA-44S-P

Input & Output

Input voltage	400V AC
Input frequency	50Hz/60Hz
Output voltage	400V AC
Max. output power	44kW
Max. output current	63A
Charging interface type	IEC 62196-2, Type 2
Connection	Plug
Cable Length	5m

Protection

Over voltage protection	Yes
Under voltage protection	Yes
Over load protection	Yes
Short circuit protection	Yes
Earth leakage protection	Yes
Over-temp protection	Yes
Lightning protection	Yes

Function & Accessory

Ethernet/WIFI/4G	Yes/Yes/Opt
LCD	Yes
RCD	Type A + 6mA DC fault current protection (Equivalent to Type B)
Charging mode	APP/RFID/Plug and Charge
LED Indicator light	Yes
Emergency stop button	Yes
Intelligent power adjustment	Opt

Working Environment

Protection degree	IP65
Operating temperature	-25°C ~+50°C
Relative humidity	5%-95% non-condensing
Maximum altitude	2000m
Cooling	Natural air cooling
Standby power consumption	<8W

Mechanical

Dimension (W/H/D)	295/466/189mm
Weight	<16kg

Mounting Accessories

Wall-mounting bracket/Ground-mounting pole	Yes/Opt
Certificate	CE