

# EVD-60D

DC Charging Station



LEADING - EDGE TECHNOLOGY

Large capacity DC charger for public charging station, dual CCS or CCS/CHAdeMo plugs

## Features



*Programmable charging mode*



*7 inch touch screen*



*Comprehensive protection*



*EU and Jap standard*



*Multiple communication modes*



*Dual output ports*

**Shenzhen AteSS Power Technology Co.,Ltd**

1st Floor of Building 3 at Sector B and 3rd Floor of Building 9,Henglong Industrial Park, No.4 Industrial Zone, Shuitian Community, Shiyan Street, Baoan District, Shenzhen

# Datasheet

## EVD-60D

### Input & Output

Input voltage	260~457V AC
Rated input voltage	400V AC
Frequency	50Hz/60Hz
DC plug type	CCS Type 2(default), CHAdeMO(opt), double plugs
Output voltage range	CCS(150-750V), CHAdeMO(150-500V)
Max. output power	60kW
Max. output current	CCS 150A, CHAdeMO 125A
Voltage accuracy	<±0.5%
Current accuracy	≤±1%(at 20%~100% of rated power)
Voltage-regulating accuracy	<±0.5%
Current-regulating accuracy	≤±1%
Ripple coefficient	RMS: ≤±0.5%; Peak: ≤±1%
Metering accuracy	0.5%
Efficiency	≥95.2%
Cable Length	5m

### Protection

Over voltage protection	Yes
Under voltage protection	Yes
Over load protection	Yes
Short circuit protection	Yes
Earth leakage protection	Yes
Over-temp protection	Yes
Lightning protection	Yes

### Function & Accessory

Display	7 inch touch screen
Ethernet/WIFI/4G	Yes/Yes/Opt
Charging mode	APP/RFID/Plug and Charge
Indicator	Yes
Emergency stop	Yes

### Working Environment

Protection degree	IP54
Operating temperature	-25°C ~+50°C
Relative humidity	5%-95% non-condensing
Maximum altitude	2000m
Cooling	Forced air cooling
Standby power consumption	<25W
Noise emission	≤65db

### Mechanical

Dimension (W/H/D)	600/1883/743mm
Weight	250kg

### Certificate

Certificate	CE
-------------	----