



## Flexible Expansion

Maximum support for 10 machines in AC parallel, expandable to 3.1MWh; support DC expansion.



## Ultra Safe

Triple-level fire suppression + active exhaust + passive explosion-proof design to eliminate hidden hazards and ensure safe operation.



## **Smart Temperature Control**

PACK smart Liquid Cooling + PCS smart Air Cooling Technology,cluster-level temperature difference ≤ 1.5°C,Energy efficiency improved by 2%



# Ultra-high Level Protection

PACK+PCS IP65,C3/C5 Anti-corrosion grade optional,Handles harsh environments such as high humidity and salt spray corrosion with ease.



# Intelligent O&M

Al+ Intelligent digital monitoring platform, Proactive strategy optimization and troubleshooting

# Specification

Model	DH300Y
Battery	
Battery Type	LiFePO₄
PACK Configuration	1P52S
PACK Quantity	5 PACK/Cluster
Rated Current	300A
Max. Current	375A
Voltage Range	754~936Vdc
System Capacity	312kWh
AC (On-grid)	
Rated Power	125kW*2
AC Maximum Current	400A
AC Rated Voltage	400Vac
Wiring Method	3P4L+PE
Frequency	50Hz/60Hz
Power Factor	O.8 (Leading)~O.8 (Lagging)
THDi	≤3% (Rated power)
System	
Weight	Approx. 3200kg (TBD)
Dimension (W/D/H)	1560/1400/2480mm (TBD)
Max. Efficiency	≥88% (TBD)
Liquid-cooling Power	10kW (Cooling) (TBD)
Temperature	-20~50℃ (Derating above 45℃)
Humidity	O~95%RH (Non-condensing)
Ingress Protection	IP55
Anti-corrosion Grade	C3/C5
Cooling Method	Battery Liquid-cooling + PCS Air-cooling
Noise	≤75dB (TBD)
Elevation	3000m (Derating above 2000m)
Display	Touch screen
Fire Protection	Aerosol (Optional Perfluorohexanone)
Communication	Ethernet/4G/RS485
Certification	CQC, CE, TUV

